

# uniseal Wall Coating



Uniseal® Wall Coating System is a 100% water-based acrylic elastomeric coating for exterior walls, providing waterproofing, crack coverage, and a durable, decorative finish in various colors.

## APPLICATIONS:

- Exterior walls
- New and existing surfaces

## BENEFITS:

- Waterproof and crack-resistant
- Durable and decorative
- Wide range of colors



Tech Specs	UOM	Uniseal® Wall Coating
Material		Water based
Colour	Standard	White
	Enquiry	Others
Pack Size	l	20
Flexibility (Mandrel)	mm	3
Impact Resistance	kg/m <sup>2</sup>	1.04
Water Vapour Transmission	g/m <sup>2</sup> /hr	1.04
Flash Point	°C	No Flammable
UV Exposure	Grey Scale	No disintegration, blisters, peeling, swelling, cracks or crazing (1000 hrs)
Chemical/Bacterial Resistance		Resistant from Algae, Fungi, Dilute organic acids, mineral & vegetable oil
Application:		5 coats
Nominal Film Thickness	mm	0.36
Nominal Coverage	m <sup>2</sup> /l	1.4
Tensile Strength	MPa	4
Elongation @ break	%	90.8
Adhesion Strength	MPa	1.4
Drying Time:	hr	1/2 to 1
Curing Time	day	7